

# Automatic Shrink & Seal Packing Machine

**LA-5000T / 6000T**

## Features:

1. Automatic L-Sealer and tunnel combo design, very compact, save space.
2. Choice of vertical or horizontal-type photocell sensor to suit various product size and thickness.
3. Kissing belt function, able to pack small product, single or multiple packages.
4. Balanced heating elements (with separate temperature regulation)
5. Color touch screen combined with PLC control, easy to use.
6. Shrink tunnel adopts advanced heater bank and adjustable high speed blower to realize re-circulating hot air, shorten the heating-up time and reduce the heat lost to ensure best shrink performance.
7. PID temperature control, temperature tolerance  $\pm 1^{\circ}\text{C}$
8. Shrink tunnel movable to make sure the products go through the center of tunnel.

## Option:

1. Printing mark registration device for printed film.
2. Additional Infeed and outfeed belt conveyor.

This is an economical solution for fully automatic shrinking & sealing packaging. It is applicable for packing all kinds of solid and regular objects, including the food, box, printing, cans, tray, hardware, etc.... Suitable for OPP,POF,PE, PVC, etc...shrink film material.



LA-6000T



LA-5000T



Shrink Packaging

## Specification

Model No.	LA-5000T	LA-6000T
Voltage supply/ Installed power	380-410 V, 3PH 6KW	380-410 V, 3PH 12KW
Compressed air pressure and consumption	6 bar;40L/min	6 bar; 90L/min
Sealing bar	480 x 450 mm	610 x 480mm
Maximum product height	100 mm	200mm
Capacity Max.	35P/min	45P/min
Speed of conveyors	10 - 25 M/min	10 - 30 M/min
Working height	800mm	800mm
Maximum size of film reel	480 - $\phi$ 280 mm	600 - $\phi$ 300MM
Machine size	2085L*1320W*H1525mm	3500L*1710W*1600Hmmm
Packed machine size	2160L* 1560W *H 1570mm	3600L*1830W*1800Hmmm
Machine weight(NW/GW)	680/825	890/1040