

# Servo Driving Horizontal Flow Wrapper

**AHP-400S / AHP-500-3S**



This wrapper is applicable for packing all kinds of solid and regular objects, including the foods such as biscuit, bread, instant noodle, ice cream, moon cake and soft sweets, and other objects such as toilet soap, medicated essence, note book, pen pack, tape and medicines in regular shapes.



## Features

1. Advanced PLC control system combined with 5.7" Colorful touch screen control panel, can easily set and change packing parameters, display production data and self-diagnostic machine error can be viewed directly from the screen.
2. Servo driving system, film speed automatically synchronized with conveyor speed
3. End seal jaw speed adjustable by a hand wheel when bag length change.
4. All parts are built for easy maintenance and cleaning.
5. Pulling wheels open by means of pneumatic switches. The sealing wheels open automatically at every machine stop.
6. Safety guards as required by European law. Comply with CE standard.
7. On all Machines is possible to install: Photocell for printed film, Printer for date, line shaft for automatic feeders, etc.

## Technical parameters

Model No.	AHP-400S	AHP-500-3S
Wrapping speed:	up to 100 pcs/min.	up to 250 pcs/min.
Max. Film reel width:	400mm	500mm
External film reel dia.:	350mm	350mm
Max. package height:	70mm	100mm
Max. package width:	200mm	200mm
Min. package length:	60mm	76mm
Max. package length:	452mm	564mm
Compressed air pressure:	6bar	6bar
Supply voltage :	220-240v1ph	380-400v3ph
Power consumption :	2.5kw	3.0kw

	AHP-400S				AHP-500-3S			
	φ114		φ144		φ144		φ174	
	1SP	2SP	1SP	2SP	1SP	2SP	1SP	2SP
Max. Length (mm)	357	178	452	226	452	226	564	273
Min. Length (mm)	120	60	151	75.3	151	75.3	182	91
Max. Height (mm)	40	40	70	70	70	70	100	100

\*The Max. Measures cannot be obtained all three together